



## DURACOAT TEK SILK

### PRODUCT DESCRIPTION

Duracoat Tek Silk is based on 100% Acrylic Emulsion and is extremely durable due to the stipple coating. Duracoat Tek Silk produces a high build stipple coating that is fully washable and is suited for high traffic areas like hallways, corridors, reception areas, exterior facades etc.

### FEATURES

- Gives good opacity
- Excellent adhesion
- Due to its high build stipple finish it also hides surface imperfections
- The pure acrylic resin confers exceptional weather resistance resulting in a long life protection of external building surfaces
- Enhanced with two potent algaecides and preservatives for dry film protection which will resist mould and algae growth
- Excellent UV and weather resistant
- Does not retain dirt, cleans easily
- Virtually odour free, user and environmental friendly

### TECHNICAL DATA

**FINISH:** Duracoat Tek Silk

**SPREAD RATE:** 7-10 Sq.Mt/ltr

**COLOURS AVAILABLE:** Over 7000 colours

**PACK SIZES:** 1litre, 4litres, 20litres

**WASHABILITY:** Easy-to-clean

### SURFACE PREPARATION

Surface should be free from any loose paint, dust and grease. Growths of fungus, algae or moss should be removed by wire brushing and water. Any surface cracks or holes should be raked out and filled with Duracoat Supafix Crackfiller (Interior) or the Duracoat Permafill Flexible Crackfiller(Exterior). Treat surface for moulds and algae if present with Duracoat Fungicidal Wash.

In the case of highly alkaline fresh masonry, apply the Duracoat Alkali Resistant Primer to provide excellent adhesion and integrity. The primer forms a barrier over alkali substrates limiting the reaction with atmospheric Carbon Dioxide thus reducing the formation of unsightly white deposits

or "efflorescence,"

**New and Unpainted Surfaces:** Surface to be painted must be clean, dry and free from grease and other impurities. Apply a coat of Duracoat Penetrating Primer. Leave to dry for 24hours. Apply one coat of Real Rock Tek Silk.

### PAINT APPLICATION PROCESS

**Product:** Duracoat Tek Silk

**Thinner:** DO NOT THIN

**Ratio:** N/A

**Application:** Textured Roller

**Drying Time: Touch dry:** 2 hours **Recoat:** 12-24 hours

### COLOUR RANGE:

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

### COLOUR VISUALISER

Choosing the right combination of shades for your home can be difficult. It is at these times that you need professional help.

Duracoat has the Colour visualizer. Choose one colour from the visualiser, pick a wall to transform and play around to get the correct colour transformation. Visit our website: [www.bascopaints.com](http://www.bascopaints.com) for more of this service.

### PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION