



## DURACOAT TILE GROUT (WHITE, GREY)

### PRODUCT DESCRIPTION

Duracoat Tile Grout is a particularly fluid form of concrete used to fill gaps. It is a cement based fine powder filler for tile joints. It contains special binder, water proofing and efflorescence reducing additive and inert aggregates.

### FEATURES

- Water proof
- Excellent workability (open time)
- High bond strength
- Mould resistant
- Non-toxic

### TECHNICAL DATA

**FINISH:** Homogenous Paste

**SPREAD RATE:** 0.25 kg/mtr

**COLOURS AVAILABLE:** Grey, white and beige

**PACK SIZES:** 1 kg and 3 kgs

### SURFACE PREPARATION

**CLEANING:** The substrate must be cured, mechanically strong, free from loose particles, grease, oils, paint, wax and sufficiently dry. All surfaces must be as flat as possible.

**MIXING:** Add 0.75- 1 litre of clean water to suitable mixing container. Slowly add 3 Kgs bag of Duracoat Tile Grout to water and mix until a homogenous lump free paste is achieved.

DO NOT add extra water or other ingredients after mixing.

Apply Duracoat Tile Grout to the gap between tiles using a sponge or a piece of cloth. Work the paste into the joints and around the edges. Remove excess grout from the face of the tile using dry cloth. When the grout is completed, polish tiles with dry cloth.

### PAINT APPLICATION PROCESS

**Product:** Duracoat Tile Grout

**Nature:** Cementitious Powder

**Application:** Spatula or Trowel

**Drying Time:** 6 hours

**Mixing Ratio:** 5-6 litres water to 25 kgs bag

### PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advise.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

**DISCLAIMER:** The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**  
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION