



DURACOAT VARNISH STAIN

PRODUCT DESCRIPTION

Duracoat Varnish Stain is available in gloss and matt finish, formulated for use on all types of timber. It is also recommended for use on newly sanded floors and timber ceilings.

FEATURES

- Preserves and enhances wood grain
- Excellent adhesion
- Good penetration
- Easy to apply

TECHNICAL DATA

FINISH: Matt or Gloss

SPREAD RATE: 14-16 Sq.Mt/ltr

COLOURS AVAILABLE: Mahogany, Walnut, Light Oak, Mid Oak and Dark Oak

PACK SIZES: 1 litre & 4 litres

SURFACES PREPARATION

Surface should be free from any loose particles, dust and grease. Growths of fungus, algae or moss should be removed by wire brushing and wiped out with Duracoat White Spirit. Any surface cracks or holes should be raked out and filled with appropriate wood filler.

All traces of wax or oil should be removed by power sanding particularly if wax had been used on the surface before.

This is a one pack, both stain and Varnish designed for all types of timber.

New Surfaces: Rub down the surface and clean with Duracoat White Spirit. Apply one coat of Duracoat Varnish Stain and let it dry. Lightly sand and clean the surface and apply two more coats.

Previously Varnished Surfaces: Remove all loose and flaking varnish, sand down and apply two coats of Duracoat varnish Stain.

Previously Painted Surfaces in Poor Condition: Remove all previous varnish by sanding the prepared surface as above and apply three coats of Duracoat Varnish Stain as new surfaces above.

PAINT APPLICATION PROCESS

Product: Duracoat Varnish stain-Gloss or Matt

Thinner: Ready-to-use/ Duracoat White Spirit

Ratio: To sprayable viscosity

Application: Brush, Spray or Cloth rag

Drying Time: 2-4 hours **Recoat:** 12 hours

When applying by spray, thin to sprayable viscosity using Duracoat White Spirit.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advice.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION