



DURACOAT VINYL MATT DELUXE EMULSION

PRODUCT DESCRIPTION

New improved formula based on advanced pure acrylic binder technology which provides long-lasting matt finish with excellent resistance to dirt pick up. Duracoat Vinyl Matt Deluxe emulsion is suitable for new and previously painted surfaces on cement, plaster, brick, ceilings hardboards, and soft boards.

FEATURES

- 5 Years Warranty
- Excellent Outdoor Durability
- Does Not Retain Dirt
- Provides a Mildew Resistant Coating
- Easy to Clean
- Smooth and Rich Matt Finish
- Excellent Adhesion
- Outstanding Protection against UV Rays
- Long Lasting Fresh Appearance
- Self-Priming
- Non Toxic

RECOMMENDED FOR

Residential and commercial applications where a matt finish with the highest performance characteristics are desired. It is an ideal interior and exterior matt finish product.

LIMITATIONS

Do not apply when air and surface temperatures are below 10°C and above 35°C.

TECHNICAL DATA

SPREAD RATE: 13- 15 Sq. Mt/ltr when applied on a smooth plaster. Coverage is considerably reduced when coating over rough surface.

FINISH: Matt

SPREAD RATE: 12 - 14 Sq. Mt/Ltr when applied on a Smooth Plaster

DRYING TIME: Surface Dry: 20 - 30 mins **Recoating Time:** 3 hours

APPLICATION: By Brush, Rollers, Conventional Spray

THINNING: Up to 30% (Vol.) water if applied by brush or roller. If applied by spray, more water may be needed to adjust to sprayable viscosity.

VOLATILE ORGANIC COMPOUNDS (VOC) : < 30gms/ltr*

COLOUR RANGE:

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

SPECIAL COLORS

Special colors can be made available on request.

SURFACE PREPARATION

All surfaces to be painted must be clean, dry and free from dust, grease or any loose material.

New Unpainted Cement or Plaster Surfaces: If the surface is dry and absorbent, apply one coat of Duracoat Alkali Resistant Primer or Duracoat Universal Undercoat. Follow up with 2-3 coats of Duracoat Vinyl Matt Deluxe Emulsion with recommended thinning.

Previously Painted Surfaces: If the existing paint work is in good condition, then the surface should be cleaned, rubbed down and 2-3 coats of Duracoat Vinyl Matt Deluxe Emulsion applied.

Brick and Asbestos Surfaces: These should be sealed with one coat of Duracoat Acrylic Sealer to reduce absorption followed by 2-3 coats of Duracoat Vinyl Matt Deluxe Emulsion Paint.

For a Smooth and Uniform Finish, use Duracoat Smotex Lite or Duracoat Internal and External Skimcoat for Skimming.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advice.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

APPLICATION

- Stir thoroughly before and during use.
- Always use a good quality brush.
- Try to paint in one motion.
- Always pretest on a small area first.

NOTE

- When over coating a dark shade with a light shade, three coats may be required.
- On Dark Shades, for example, Bright Reds, Greens, Oranges, an additional coat will be required as some have low opacity.

POST APPLICATION INSTRUCTIONS

- The best way to remove wall stains is to remove them immediately.
- To remove wall stains, sponge clean with a mild soap/detergent solution and wipe clean.
- For better washability ensure the painted surface is cured for 1 week.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION