



DURACOAT ROYALE VINYL SILK SHEEN EMULSION

PRODUCT DESCRIPTION

Duracoat Royale Vinyl Silk Sheen Emulsion is technically upgraded, superior premium emulsion paint with high quality resin, pigments and extenders.

FEATURES

- Excellent durability
- Virtually odour free, environmentally friendly
- Better coverage and improved opacity
- High scrub resistance: For areas with a high traffic
- Suitable for schools, hotels, restaurants, hospitals, public buildings, etc.
- Excellent stain resistance

TECHNICAL DATA

FINISH: Attractive subtle reflective sheen

SPREAD RATE: 14-17 Sq.Mt/Ltr

COLOUR AVAILABLE: Over 7000 shades

PACK SIZES: 1 litres, 4 litres, 20 litres

WASHABILITY: Easy-to-clean

SURFACE PREPARATION

Surface should be free from any loose paint, dust and grease. Growths of fungus, algae or moss should be removed by wire brushing and water. Any surface cracks or holes should be raked out and filled with Duracoat Supafix Crackfiller (Interior). Treat surface for moulds and algae if present with Duracoat Fungicidal Wash.

In the case of highly alkaline fresh masonry, apply the Duracoat Alkali Resistant Primer to provide excellent adhesion and integrity. The primer forms a barrier over alkali substrates limiting the reaction with atmospheric Carbon Dioxide thus reducing the formation of unsightly white deposits or "efflorescence."

New And Unpainted Surfaces: Ensure the surface is dry. Apply one coat of Duracoat Royale All Purpose Undercoat followed by 2 coats of Duracoat Royale Vinyl Silk Sheen Emulsion.

PAINT APPLICATION PROCESS

Product: Duracoat Royale Vinyl Silk Sheen Emulsion

Thinner: Clean Water.

Ratio: 10% on both coats

Coats: 3 coats for best results

Application: Brush, Roller or Spray

Drying Time: Touch dry: 45 minutes

Recoating time: 4-5 hours

COLOUR RANGE

Available in a wide range of colors from the Duracoat Color Chart, Duracoat Classic Fandec and Duracoat Color Plus Fandec.

COLOUR VISUALISER

Choosing the right combination of shades for your home can be difficult. It is at these times that you need professional help. Duracoat has the Colour Visualiser. Choose one colour from the visualiser, pick a wall to transform and play around to get the correct colour transformation. Visit our website: www.bascopaints.com for more of this service.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Store the product at ambient conditions in well ventilated locations and away from sources of ignition and fire.
- Avoid eye and skin contact. In case of eye and skin contact, wash with plenty of clean water. If symptoms persist, seek medical advice.
- Do not inhale or ingest. In case of inhalation, move to fresh air and seek medical attention if symptoms persist in both the cases.
- Use appropriate personal protective equipment.
- In high humidity areas, use of a bio wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of the paint system.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION