



NGUVU GRIP TILE ADHESIVE

PRODUCT DESCRIPTION

Nguvu grip tile adhesive is a cementitious, non-shrink, general purpose Tile Adhesive. It contains the highest grades of Cement, Fillers, Polymers and Chemical Additives to give it unique adhesion properties.

RECOMMENDED FOR

Nguvu Grip Tile Adhesive is suitable for fixing Wall and Floor tiles, Terrazo tiles, Mosaic tiles and Granite tiles

FEATURES

- Excellent workability (Open Time)
- Easy to use at site
- High bond strength
- Can be applied directly on cement screeds, concrete or lime mortars
- Suitable for indoor and Outdoor application
- Non-toxic

TECHNICAL DATA

NATURE: Cementitious Powder

COLOR: Grey

DENSITY: 1.9 kg/ltr

OPEN TIME: Approximately 30 mins at 25°C

POT LIFE: Approximately 60 mins at 25°C

MIXING RATIO: Approximately 5-6 ltrs for 25 kgs bag

COVERAGE: Approximately 3-4 kg / Sq.Mt/ltr

TEMPERATURE: Min 5°C, Max 4°C (Substrate)

PACKAGING: 25 Kg bag

SUBSTRATE PREPARATION

The substrate must be cured, mechanically strong, free from loose particles, grease oils, paint, wax and sufficiently dry. All surfaces must be as flat as possible.

MIXING

Add 5-6 ltrs of clean water to a suitable mixing container. Slowly add Nguvu Grip Tile Adhesive Powder to the clean water and mix until a homogeneous lump-free paste is achieved. Do not add extra water or other ingredients after mixing.

APPLICATION

Apply Nguvu Grip Tile adhesive 2-3 mm thickness directly to the concrete substrate using a notched trowel and spread the mortar evenly over the area to be tiled. Fix tiles immediately within the open time for 30 minutes. Carry out random check to determine whether the back of the tile is full covered with Nguvu Grip Tile Adhesive. To ensure that the open time has not lapsed, check if the Nguvu Grip Tile Adhesive Mortar still adheres to your finger in order to avoid bonding failure. If the open time has lapsed, remove the applied adhesive layer and apply a fresh layer to continue further tiling.

DISCLAIMER: The information and recommendation set forth in this Product Data Sheet are based upon tests conducted by Basco Products (K) Ltd. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Basco Products (K) Ltd. Representative to obtain the most recent Product Data Information.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
 REFER TO MSDS FOR ADDITIONAL HEALTH AND SAFETY INFORMATION